



Buggy Silent Meat Cart



- Eliminates excessive noise
- Optimum hygiene easy washdown
- Multiple colours for colour coded zones
- Very low weight of 22 kg

- German standards
- Same dimensions as standard steel buggy
- Unique triple-wall PE construction
- EU/FDA food-grade approved materials



Silent 200 Buggy

The lightweight and silent solution

The Buggy meat cart is the first of its kind. It is developed to meet the requirements of the food industry and is based on the German standard DIN 9797.

Compared to stainless steel, the Buggy offers a wide range of advantages.

- Light weight ensures easy handling
- Rotationally moulded, no welds and optimal hygiene
- Smooth surface improves cleaning
- Considerable noise reduction
- Color coding for increased food safety

The Buggy is built to withstand the harsh conditions and rough handling in meat and other food processing. The sturdy undercarriage has hard-wearing nylon wheels with polyurethane tread. Stainless steel lifting brackets are integrated to facilitate thorough cleaning.


The Buggy is ideally suited for the handling of wet and dry meat products and a wide variety of other food products with a working capacity of 200 litres.

It's very low weight of 22 kg allows for easy handling. The ergonomically designed handles give a high degree of maneuverability.

The triple-wall polyethylene Buggies absorb noise whereas its counterpart stainless steel creates the usual noise pollution. The sound level during dumping is diminished by 17 dB. Our Buggy helps to reduce the risk of hearing disorders.


The versatile Buggy is available in four colours.







Ergonomically designed handles.



Integrated grip for easy lifting



Integrated stainless steel brackets.

Model	Outer Dimensions in cm			Inner Dimensions in cm			Weight	Volume
	L	W	Н	L	W	н	Kg	Liters
SÆPLAST 185 Buggy	80	68	70	58–66	56–62	49	23	185
SÆPLAST 200 Buggy	82	72	70	56–64	56–64	52	22	200

SÆPLAST products are constructed from EU/FDA approved food-grade materials. Dimensions and weights are +/- 2% Temperature tolerances range from -30°C to +60°C. For cleaning max. 70°C.







SÆPLAST ASIA - PART OF RPC GROUP • HONG KONG • TAICANG • Mainland China Tel: +(86) 512 5320 0633 www.saeplast.com • asia@promens.com

